

ZKBio550W

All in One Biometric Smart POS Terminal



Features

- Power-efficient Intel® Core™ i5-4200U Processor (1.6 GHz up to 2.6 GHz) Quad-Core processor
- 15.6" Bezel-Free true-flat display with PCAP touch
- Multiple I/O interfaces for peripherals
- Standard with 2G RAM and 32G SSD
- Optional 3 tracks MSR, attached VFD&11.6" customer display
- Faster installation and maintainability

Optional



Magnetic Stripe
Card Reader



2nd LCD Display Screen



Mifare/RFID



Thermal Printer



Cash Drawer



VFD Customer Display

Specifications

Model number	ZKBio550W
System	
Processor	Intel® Core™ i5-4200U Processor (1.6 GHz up to 2.6 GHz)
System Memory	4GB Standard, DDR3L 1333MHz
Storage Device	64GB Msata SSD Standard, 1*2.5" HDD / 2.5" SSD
OS Supported	Windows 7, Windows 8, Windows 10 IoT Enterprise, POS Ready 7, Linux
Audio	Realtek ALC662
Display and Touch	
Type	15.6" TFT LCD, LED Backlight
Resolution	1920*1080
Touch Screen	Projected Capacitive
External I/O Ports	
VGA	1*DB-15
USB	5*USB2.0, 1*USB3.0
Serial	1*RS232(Max.4pcs)
LAN	1*RJ45
Audio	1*Line-out
Power	
Power Supply	Adaptor 12V DC 5A
Physical Environmental	
Operating Temperature	0°C ~ 35°C at 20%-80% Humidity
Storage Temperature	- 20°C ~ 55°C at 20%-80% Humidity
Dimensions(W×H×D)	490*300*420mm
Net Weight	5.9kg
Certification	CE FCC
Color	Black
Second Display	11.6" TFT LCD
Customer Display(VFD)	VFD(2*20 lines)



V1.0 2020.6.24

ZKTECO CO.,LTD.

www.zkteco.com

E-mail: sales@zkteco.com



Copyright©2019 ZKTECO CO., LTD. All rights reserved.